Bostik All Season Gun

Replaces date: 16/11/2016 Revision date: 21/11/2019

SECTION 1: Identification of the substance/preparation and of the company/undertaking

1.1. Product identifier

Trade name: Bostik All Season Gun

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended uses: 1-component polyurethane foam.

1.3. Details of the supplier of the safety data sheet

Supplier

Company: Bostik AB

Address: Strandbadsvägen 22

Zip code: 251 09

City: Helsingborg

Country: SWEDEN

E-mail: info.se@bostik.com

Phone: +46 42 19 50 00

Homepage: www.bostik.com

Contact person: Name: Environment dep., Phone: +46 42 19 50 00

1.4. Emergency Telephone Number

112 - ask for Poison Information Center - Sweden

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLP-classification: Aerosol 1;H222 Aerosol 2;H229 Acute Tox. 4;H302 Skin Irrit. 2;H315 Skin Sens. 1A;H317

Eye Irrit. 2;H319 Resp. Sens. 1B;H334 STOT SE 3;H335 Carc. 2;H351 STOT RE 2;H373

Most serious harmful effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful if

swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs

through prolonged or repeated exposure.

2.2. Label elements

Pictograms



Signal word: Danger

Contains

Substance: Diphenylmetanediisocyanate, homologous and isomers; isobutane; Phosphoric trichloride,

Bostik All Season Gun

Replaces date: 16/11/2016 Revision date: 21/11/2019

reaction products with propylene oxide; Dimethyl ether

H-phrases

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.
H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

P-phrases

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 Wear respiratory protection.

P308+313 IF exposed or concerned: Get medical advice/attention.

P410+412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/ container to an approved waste disposal plant.

Supplemental information

EUH204 Contains isocyanates. May produce an allergic reaction.

*Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. Please use the attached protective gloves! Throw away after use, do not re-use.

2.3. Other hazards

The components in this product do not meet the criteria for classification as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	CAS No	EC No	REACH Reg. No.	Concentration	Notes	CLP- classification
Diphenylmetane diisocyanate, homologous and isomers	9016-87-9	618-498-9		30 -< 50%		Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319 Acute Tox. 4;H332 Resp. Sens. 1;H334 STOT SE 3;H335 Carc. 2;H351 STOT RE 2;H373
isobutane	75-28-5	200-857-2	01-2119485395- 27	10 -< 20%		Flam. Gas 1;H220 Press. Gas Comp. gas;H280
Phosphoric trichloride, reaction products with propylene oxide	-	911-815-4	01-2119486772- 26-XXXX	10 -< 20%		Acute Tox. 4;H302 Acute Tox. 4;H332
Dimethyl ether	115-10-6	204-065-8	01-2119472128- 37	5 -< 10%		Flam. Gas 1;H220 Press. Gas Comp. gas;H280
propane	74-98-6	200-827-9	01-2119486944- 21	1 -< 2.5%		Flam. Gas 1;H220 Press. Gas Comp. gas;H280

Bostik All Season Gun

Replaces date: 16/11/2016 Revision date: 21/11/2019

butane	106-97-8	203-448-7		1 -< 2.5%	Flam. Gas 1;H220
Morpholine, 4,4'- (oxydi-2,1- ethanediyl)bis-	6425-39-4	229-194-7	01-2119969278- 20	0.1 -< 1%	Skin Irrit. 2;H315

Please see section 16 for the full text of H-phrases.

Ingredient comments: This product does not contain candidate substances of very high concern at a

concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Move the exposed person to fresh air at once. When unconscious, loosen tight clothing

and position in secured sideposition. Call for medical attention/ambulance.

Ingestion: Seek medical advice immediately. Show this safety data sheet, if possible. Do not induce

vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn''t enter the lungs. If swallowed, rinse mouth with water (only if the person is conscious).

Skin contact: Remove contaminated clothing. Wash the skin thoroughly with water and continue washing

for a long time. Wash skin thoroughly with soap and water. Seek medical attention in case

of serious injuries.

Eye contact: Open eye wide, remove any contact lenses and flush immediately with water (preferably

using eye wash equipment). Seek medical advice immediately. Continue flushing until

medical attention is obtained.

General: In the event of an accident, nausea or other effect, contact a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Risk of allergic reaction, with breathing difficulties of asthma type. Contact with the skin may cause irritation and allergic contact eczema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Fire may be extinguished using powder, foam or carbon dioxide (CO2).

Unsuitable extinguishing

media:

DO NOT USE WATER!

5.2. Special hazards arising from the substance or mixture

Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released.

Bursting aerosols can be forcibly projected from a fire.

5.3. Advice for fire-fighters

Wear a self contained breathing apparatus.

Other Information: Containers close to fire should be removed immediately or cooled with water.

SECTION 6: Accidental release measures

Bostik All Season Gun

Replaces date: 16/11/2016 Revision date: 21/11/2019

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: If large amounts are released, the use of protective equipment may be advisable. Avoid

direct contact. Use only in well-ventilated areas.

For emergency responders: No action shall be taken that involves personal risk or without appropriate training. The

surrounding area must be removed. Keep unnecessary and undeclared workers away. Do not touch or walk through chemicals. Use suitable protective equipment. Show this safety

data sheet if possible.

6.2. Environmental precautions

Avoid discharge into drains, water or soil.

6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent, non-combustible material and transfer to suitable waste containers. In the event of major emissions, contact the relevant authorities.

6.4. Reference to other sections

See section 13 for waste disposal. See Sections 7 and 8 for prevention.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin, eyes or clothing. See section 8 for type of protective equipment.

People with impaired lung function or distinct susceptibility to allergies should not work with isocyanates. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Keep out of reach of children.

All work must be carried out under well-ventilated conditions. Wash hands before breaks, before using restroom facilities, and at the end of work. Do not eat, drink or smoke during work.

7.2. Conditions for safe storage, including any incompatibilities

Store in a dry, cool, well-ventilated area. Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Aerosols can explode when heated to temperatures over 50 °C.

7.3. Specific end use(s)

The product should be used only for the purposes specified to the manufacturer. See Product Data Sheet.

Other Information: Anyone working with isocyanate products must undergo special training and a specific

medical examination.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit

Substance name	Time period	ppm	mg/m3	fiber/cm3	Comments	Remarks
Diphenylmetan ediisocyanate, homologous and isomers	8h		0.02			SEN
Diphenylmetan ediisocyanate, homologous and isomers	15m		0.07			SEN

Bostik All Season Gun

Replaces date: 16/11/2016 Revision date: 21/11/2019

SEN = Capable of causing respiratory sensitisation

8.2. Exposure controls

Exposure controls: All work must be carried out under well-ventilated conditions. Wash hands before breaks,

> before using restroom facilities, and at the end of work. Do not eat, drink or smoke during work. A respirator must be used if the concentrations exceed the hygienic limit values.

Appropriate engineering

controls:

Technical measures: Ensure good general ventilation standards. use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below limits. Personal Precautions: Avoid skin contact with the product, wipe up the pollution / spills as soon as they arise. Wear gloves (tested to EN374) if hand contamination, wash away the impurities of the skin immediately. Wear suitable Coveralls protect against skin exposure. Provide basic training for employees to prevent / minimize exposures.

eye/face protection:

Personal protective equipment, Use approved safety goggles or face shield.

skin protection:

Personal protective equipment, Wear appropriate clothing to prevent any possibility of skin contact.

hand protection:

Personal protective equipment, Protective gloves: Suitable material for protective gloves; EN 374, Polycloroprene - CR: Thickness> = 0.5mm; Breakthrough time> = 480min. Nitrile rubber - NBR: Thickness> = 0.35mm; breakthrough time> = 480min. Fluorum rubber - FKM: Thickness> = 0.4mm; Breakthrough time> = 480min. Change gloves immediately if contaminated, and wash hands with soap and water.

respiratory protection:

Personal protective equipment. In insufficiently ventilated workplaces and during spraying, respiratory protection is required. A compressed air mask is recommended, or combination filter A2-P2 for short-

term work.

Environmental exposure

controls:

Ensure compliance with local regulations for emissions.

Heating hazards: Aerosols can explode when heated to temperatures over 50 °C.

Other Information: Provide shower facilities near the work place. Isolate contaminated clothing and wash

before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Parameter	Value/unit
State	Aerosol
Colour	Yellowish white.
Odour	No data
Solubility	No data
Explosive properties	No data
Oxidising properties	No data

Parameter	Value/unit	Remarks
pH (solution for use)	No data	
pH (concentrate)		
Melting point	No data	
Freezing point	No data	
Initial boiling point and boiling range	- 12 °C	
Flash Point	- 83 °C	(Propellant)
Evaporation rate	No data	
Flammability (solid, gas)	No data	
Flammability limits	No data	
Explosion limits	No data	
Vapour pressure	< 300 kPa	

Safety Data Sheet Bostik All Season Gun Replaces date: 16/11/2016 Revision date: 21/11/2019 Vapour density No data Relative density 0.97 Partition coefficient n-octonol/water No data 460 °C Auto-ignition temperature Decomposition temperature No data No data Viscosity

No data

9.2 Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Odour threshold

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

10.3. Possibility of hazardous reactions

Reacts violently with amines and alcohol. In closed vessel penetrating water may cause gas formations, pressure increase or bursting the vessel.

10.4. Conditions to avoid

Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Keep out of reach of children.

10.5. Incompatible materials

Strong alkalis. Strong acids. Oxidising agent. Reducing agent.

10.6. Hazardous decomposition products

Stable under recommended storage and handling conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Diphenylmetanediisocyanate, homologous and isomers, cas-no 9016-87-9

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LD50		> 2000mg/kg			

Phosphoric trichloride, reaction products with propylene oxide, cas-no-

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		632mg/kg			

Harmful if swallowed.

Acute toxicity - dermal

Diphenylmetanediisocyanate, homologous and isomers, cas-no 9016-87-9

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LD50		> 2000mg/kg			

Phosphoric trichloride, reaction products with propylene oxide, cas-no-

Bostik All Season Gun

Replaces date: 16/11/2016 Revision date: 21/11/2019

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LD50		> 2000mg/kg			

Acute toxicity - inhalation

Diphenylmetanediisocyanate, homologous and isomers, cas-no 9016-87-9

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LC50	4h	11mg/l			

Phosphoric trichloride, reaction products with propylene oxide, cas-no-

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
	LC50	4h	> 20mg/l			

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye

irritation:

Causes serious eye irritation.

Respiratory sensitisation or

skin sensitisation:

May cause allergy or asthma symptoms of breathing difficulties if inhaled. May cause an

allergic skin reaction.

Germ cell mutagenicity: Based on existing data, the classification criteria are deemed not to have been met.

Carcinogenic properties: Suspected of causing cancer.

Single STOT exposure: May cause respiratory irritation.

Repeated STOT exposure: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard: Based on existing data, the classification criteria are deemed not to have been met.

SECTION 12: Ecological information

12.1. Toxicity

No information available

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

No information available

12.5. Results of PBT and vPvB assessment

The components in this product do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information available

Other Information

Avoid discharge into drains, water or soil. Reacts with water during the development of carbon dioxide to solid et inextricably reaction product. (Polycarbamide).

Bostik All Season Gun

Replaces date: 16/11/2016 Revision date: 21/11/2019

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Refuse, spillages and packaging waste are treated as dangerous waste. If large quantities are handled, a chemicals protective suit with breathing apparatus should be available. Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Category of waste: 16 05 04* gases in pressure containers (including halons) containing hazardous

substances

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN-No.:195014.4. Packing group:N/A14.2. UN proper shippingAEROSOLS14.5. EnvironmentalNo

name: hazards:

14.3. Transport hazard 2 class(es):

Hazard label(s): 2.1

Hazard identification number: Tunnel restriction code: (D)

Inland water ways transport (ADN)

14.1. UN-No.:UN 195014.4. Packing group:14.2. UN proper shippingAerosol, flammable14.5. Environmental

name: Aerosoi, fiammable 14.5. Enviro

14.3. Transport hazard class(es):

Hazard label(s):

Transport in tank vessels:

Sea transport (IMDG)

14.1. UN-No.: 1950 14.4. Packing group: N/A

14.2. UN proper shipping Aerosol, flammable **14.5. Environmental** No **name:** hazards:

14.3. Transport hazard 2 Environmental Hazardous

class(es): Substance Name(s): Hazard label(s): 2.1

EmS: F-D, S-U IMDG Code segregation

Air transport (ICAO-TI / IATA-DGR)

14.1. UN-No.: 1950 **14.4. Packing group:** N/A

group:

14.2. UN proper shipping Aerosol, flammable **14.5. Environmental** No hazards:

14.3. Transport hazard 2

class(es):

Hazard label(s): 2.1

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Bostik All Season Gun

Replaces date: 16/11/2016 Revision date: 21/11/2019

Special Provisions:

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Safety, health and environmental regulations / legislation specific for the substance or mixture. EU regulation (EC) No. 1907/2006 (REACH).

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59.

The product does not contain SVHC substances.

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction:

Diphenylmetanediisocyanate, homologous and isomers [9016-87-9]. Restrictions on use:56

EU-REACH (1907/2006) - Annex XIV - List of substances subject to authorisation: None of the components are listed.

Authorisations / limitations:

People under the age of 18 must not be exposed this product. Council directive 94/33/EC.

15.2. Chemical Safety Assessment

Other Information:

*Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. Please use the attached protective gloves! Throw away after use, do not re-use.

SECTION 16: Other information

References to literature and

data sources:

* NOTE: This rule (552/2009) applies to products sold to the general public / consumers. Products that contain Diphenylmethanediisocyanatr (MDI) and used for professional and industrial use of rules for personal protective equipment as SDS for each product.

Training advice: Anyone working with isocyanate products must undergo special training and a specific

medical examination.

Vendor notes: Version 2

> The information in this SDS is based on our current knowledge and on current EU and national laws. The product should not be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the user who has full responsibility to comply with the requirements of current legislation. The information in this SDS is meant as a description of safety requirements for the product and not a

guarantee of product properties.

Date: 21/11/2019

List of relevant H-statements

H220 Extremely flammable gas. H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure, may explode if heated.

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Bostik All Season Gun

Replaces date: 16/11/2016 Revision date: 21/11/2019

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Document language: GB